

Hangstraights

CLAMP STYLE ARM MOUNT

To slip fit 8" long by 2-3/8" OD on horizontal tenon.



HSCB
Hangstraight, clamp style, BALL finial



HSCB-R-PE
Hangstraight, clamp style with BALL finial, twist-lock receptacle, photocell in decorative cap.



HSCS
Hangstraight, clamp style, SPIKE Finial



HSCS-R-PE
Hangstraight, clamp style with SPIKE finial, twist-lock receptacle, photocell in decorative cap.



HSCN
Hangstraight, clamp style, NO Finial

HORIZONTAL ARM MOUNT

To slip fit 4" long by 2-3/8" OD on horizontal tenon.



HSHB
Hangstraight, horizontal, BALL finial



HSHB-R-PE
Hangstraight, horizontal with BALL finial, twist-lock receptacle, photocell in decorative cap.



HSHS
Hangstraight, horizontal, SPIKE Finial



HSHS-R-PE
Hangstraight, horizontal with SPIKE finial, twist-lock receptacle, photocell in decorative cap.



HSHN
Hangstraight, horizontal, NO Finial

VERTICAL ARM MOUNT




EZ
"EZ Hang" vertical hangstraight.

HSHS	Standard horizontal hangstraight, spike finial
HSHN	Standard horizontal hangstraight, no finial
HSHB	Standard horizontal hangstraight, ball finial
HSCB	Clamp style horizontal hangstraight, ball finial
HSCS	Clamp style horizontal hangstraight, spike finial
HSCN	Clamp style horizontal hangstraight, no finial
EZ	Vertical hangstraight, large, "EZ" mount

Down lighting luminaires present an unusual challenge in that they are normally installed over a roadway in long linear fashion. Any irregularity in mounting the pole, arms or luminaires ends in a line of lighting fixtures that do not hang level and plumb. An otherwise beautiful project ends up looking like it was installed incorrectly.

It is nearly impossible to get every pole perfectly straight. It is nearly impossible to get every arm mounted in exactly the same way and the same goes for each luminaire so what is a contractor to do? The answer is Hangstraight from Sternberg. These simple mechanical devices allow for some lean and tilt from pole, arm and luminaire installations and compensate by providing a ball and swivel that can be leveled to the ground via gravity then positively locked in place with set screws. The end result is a perfectly straight line of beautiful Sternberg fixtures that do the lighting job they were intended to do.

EZ Hang



The EZ Hang device allows the installer a quick and easy way to hang, wire and secure a pendant mounted luminaire. The EZ Hang hardware will ensure that the installer can make adjustments for level and plumb making each project and luminaire assembly identical in appearance.



Feed power supply wires through the EZ Hang and ball aligner and into the luminaire.




Lift luminaire, with ball aligner attached, and insert ball aligner into the EZ Hang housing. The castings mate together forming a secure position for the ball to rotate.



After the ball aligner has been seated into the housing casting install the cast security cover preventing the ball aligner from being removed from the housing.



Secure cover with stainless steel screws.



Align fixture to level by placing a bubble level across the bottom of the luminaire. Plumb adjustments are automatic by letting the fixture hang straight down via the EZ Hang apparatus. Once in position the stainless fixation screw is secured in place. The luminaire will not move in any direction once the fixation screw is torqued down.